

SIM card -
easy to install



**ZONE 2/22
CL I, II, III DIV 2**

- › Ideal for IoT maintenance applications
- › Zero-touch capable
- › Android™ 13

IS930.2



The robust and powerful tablet of the Industry 4.0 generation is Android Enterprise Recommended and can be used immediately thanks to its zero-touch functionality, making it ideally suited for maintenance applications in the IoT environment. The 8-inch display, two freely programmable buttons, a long-life battery, a practical hand strap and a separate leather bag with a shoulder/belt or carry strap system are further highlights.

› Android is a trademark of Google LLC. All trademarks and copyrights are the properties of their respective owners. › © 2024 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1041MD01REV14_EN_10.2024



< IS930.2 >



ATEX approval: EX-Zone 2/22
Ⓢ II 3G Ex ic IIC T4 Gc IP64
Ⓢ II 3D Ex ic IIIC T135°C Dc IP64



IECEx approval: EX-Zone 2/22
Ex ic IIC T4 Gc IP64
Ex ic IIIC T135°C Dc IP64



NEC500 approval:
Class I, II, III Division 2
Groups A B C D F G T4 T135°C



EAC approval:
2Ex ic IIC T4 Gc X
Ex ic IIIC T135°C Dc X

TECHNICAL FEATURES

| | |
|----------------------------|---|
| Operating system | Android™ 13 |
| Processor | SDM660 Octa-Core |
| Memory | 4 GB RAM 64 GB internal memory microSD memory up to 512 GB |
| Frequencies | 2G GSM: 850/900/1800/1900 MHz 3G WCDMA: UMTS B1/2/4/5/8 4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFBI B13/14/17/20/25/26/28A/28B/29/30/66 4G LTE-TDD: B38/B39/B40/B41 4G LTE-SCDMA: B34/B39 |
| Dimensions | size: 237 x 156 x 22 mm weight: 890 g |
| Display | 8" Gorilla Glass® 3. generation 1200 x 1920 pixels |
| Battery | 8400 mAh |
| Camera | 13 MP AF rear camera 5 MP FF front camera |
| Connections | WiFi 2,4 GHz + 5 GHz: IEEE 802.11 a/b/g/n/ac/e/k/r/h with max. 8 connections hotspot Bluetooth® 5 GPS, A-GPS, Glonass, Beidou, Galileo Near Field Communication |
| Types of protection | IP68 dust-/waterproof MIL-STD-810H usable from -20 °C to +60 °C |

FURTHER FEATURES



SOS key for loneworker protection
LWP ready (third party application required,
based on country specific regulations)



2 freely programmable keys



Usable with gloves



Accelerometer, gyroscope, magnetic,
temperature and humidity, proximity sensors



Magnetic charger port

SET CONTENT

Tablet with integrated battery, Hand Strap, Type C USB Cable, Magnetic Charger Cable, Power Adapter universal, Display Protection Foil, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.